



C-Pro Voicetrack M2

P/N: CTC-112VT



The C-Pro Voicetrack M2 is a video conferencing camera with autofocus, autoframing and intelligent voice and people tracking with Artificial Intelligence. Optical zoom of 12X and total of 192X.

Main characteristics

 Dual Camera	 1080P60	 12X optical zoom	 Voice tracking	 Auto frame
-----------------	-------------	----------------------	--------------------	----------------

Compatibilidad con:



Central offices:
Av. Cerro del Águila, 3, 1B2.
S.S. de los Reyes 28703
Madrid - Spain

US Office:
2480 Presidential Way,
unit 1104, West Palm Beach, FL.
Main office number: 561-925-5242
US Toll Free: 844-513-1770

(*) 6 years "Prime support" warranty for those products of the C-Pro, Broadcaster and Broadcaster Pro families by registering the purchase on Laia's website up to 2 months from the date of purchase.

C-Pro VoiceTrack M2 Specifications: P/N: CTC-112VT

Tracking camera

Image sensor: 2.14M Pixels. 1/2.8 inch CMOS

Video system: 1080P-30fps

Minimum illumination: 1Lux

SNR: ≥50dB

DNR: 2D & 3D

Panoramic lens

FoV: 110°

Focal length : 1.89mm

Full vision camera

Image sensor: 2.14M Pixels. 1/2.8 inch CMOS

Video system : 1080P-60fps

Video signal: HDMI/3G-SDI: 1080P-60/50/30/25/fps; USB 3.0: 1080P-60/50/30/30/25/fps; IP: 1080P-30/25/fps

Minimum illumination: 0.5Lux (Color)

SNR: ≥50dB

DNR: 2D & 3D

Backlight compensation: On/Off

Iris: F1.6□F14, CLOSE.

Shutter speed: 1/50□1/10.000

White balance: Auto/manual/single pulse/static color temperature.

Exposure mode: Auto, manual, shutter priority, iris priority, brightness.

Focal mode: Auto/Manual/Push once/Push PTZ.

Digital Zoom: 16X

Vertical and mirror flip-over: Supports

Dynamic range: Off, 1□5

Video settings: Brightness, contrast, sharpness, gamma curve.

Tracking lens

Wide-angle horizontal FoV - Telephoto: 72.5°□6.3°.

Focal length: 4.1mm-49.2mm

Optical zoom: 12X

Minimum object distance: 1.5 m

Aperture: F1.6□F2.8 ±5%.

Pan-tilt Main unit

Pan | Tilt Movement: -130°□+130° | -30°□+90°.

Pan | Tilt Speed: 0.2°/s□90°/s | 0.2°/s□60°/s

Number of presets:

Preset Speed: PAN 87°/s, TILT 66°/s.

Input/output interface

Video Outputs (connectors): 3G-SDI (BNC), HDMI (HDMI Type A), USB 2.0 (Type-A HOST), USB 3.0 (Type-B), IP (RJ45).

Compatibility/Byom

Laia myTeam Sharer/ClickShare Barco: Yes



Central offices:
Av. Cerro del Águila, 3, 1B2.
S.S. de los Reyes 28703
Madrid - Spain

US Office:
2480 Presidential Way,
unit 1104, West Palm Beach, FL.
Main office number: 561-925-5242
US Toll Free: 844-513-1770

(*) 6 years "Prime support" warranty for those products of the C-Pro, Broadcaster and Broadcaster Pro families by registering the purchase on Laia's website up to 2 months from the date of purchase.